



Power when you need it most

11,000-Watt Tri Fuel (Gas/LPG/NG) Portable Inverter Generator

Gas: 9,000 Running Watts | 11,000 Peak Watts

Propane: 8,100 Running Watts | 10,000 Peak Watts

Natural Gas: 7,200 Running Watts | 8,800 Peak Watts

POWERFUL CUMMINS ONAN 457CC ENGINE

- Runs on gasoline, propane, or natural gas for maximum fuel flexibility
- Perfect for sensitive electronics with a total harmonic distortion of less than 3 percent
- Compact, easily portable, and quieter than traditional generators, making it the perfect choice for home, recreation, or jobsite use

FEATURES

- Foldable, locking handle with easy-grip lift
- Battery charging port with charger included
- Ports for parallel generator operation
- Oil and maintenance tools included
- 3-Year Limited Residential Warranty



US Model

Not for Sale in California



PUSH BUTTON & REMOTE START

Pull cord backup



DIGITAL DATA CENTER

Digital Data Center displays remaining runtime, power, voltage, frequency, fuel level, and lifetime run hours



TRI FUEL WITH JUST THE TURN OF A DIAL

Easily switch from gas to propane to natural gas



CARBON MONOXIDE DETECTOR

Includes automatic shutoff for safer operation



ONAN P11000iT

Specifications		Gas - run time at 25% load (hrs)	16.5 hrs
Part number	A078C500	Propane - run time at 25% load (hrs) with 20-lb standard propane tank	6.7 hrs
Gasoline running watts	9,000 W	Natural gas run time at 25% load (hrs) (maintenance based)	50 hrs
Gasoline peak watts	11,000 W	Gasoline fuel gauge	Digital
Gasoline running amps	75 A @ 120 V 37.5 A @ 240 V	AC outlets	(1) Duplex GFCI 120V 20A (5-20R) (1) 120/240V 30A (L14-30R) (1) 120/240V 50A (14-50R)
Gasoline peak amps	91.6 A @ 120 V 45.8 A @ 240 V	DC outlets	(2) USB-A 5V 2.1A
Propane running watts	8,100 W	Covered outlets	Yes
Propane peak watts	10,000 W	Remote control outlet	For future accessory compatibility
Propane running amps	67.5 A @ 120V 33.8 A @ 240 V	Ground	Neutral bonded
Propane peak amps	83.3 A @ 120V 41.6 A @ 240 V	Manual transfer switch ready	Yes
Natural gas running watts	7200 W	Overload protection (circuit breaker)	Yes
Natural gas peak watts	8800 W	Handle style	Cantilevered, Lockable
Natural gas running amps	60 A @ 120 V 30 A @ 240 V	Wheel kit included	Yes
Natural gas peak amps	73.3 A @ 120 V 36.6 A @ 240 V	Wheel size	8 in (203 mm) diameter, 2 in (51 mm) wide
AC voltage	120/240 Volts	Frame thickness	1 in (25 mm)
AC frequency	60 Hz	Emissions	EPA
Total Harmonic Distortion (THD)	≤3%	Spark arrestor	Yes
Automatic voltage regulator	Inverter	Limited residential warranty	3-year
Starting system	Electric, remote, recoil	Commercial warranty	1-year
Battery Included	Yes	Assembled length	30.3 in (770 mm)
Battery charger included	Yes	Assembled width	25.0 in (635 mm)
Remote start fob included	Yes	Assembled height	27.0 in (686 mm)
Remote start distance (feet/meters)	98 ft (30 m)	Extended length	45.7 in (1,161 mm)
Push button start	Yes	Carton length	31.7 in (805 mm)
Engine displacement	457 cc	Carton width	26.2 in (665 mm)
Engine brand	Cummins Onan	Carton height	30.8 in (782 mm)
Engine type	OHV 4-Stroke	Dry unit weight	219 lb (99 kg)
Engine speed	Variable	Shipping weight	225 lb (102 kg)
Operational volume (dBA)	64 dBA	Compatible Accessories:	
> 2000ft (610m) operation	Yes: Carb & Fuel Switch kits req'd	Natural Gas Hose Kit (A069G128)	
Auto idle control	Yes	L14-30P to 4 x 5-20R Power Distribution Cord (A058U971)	
Built-in inverter	Yes	L14-30P to L14-30R Transfer Switch Cord (A058U96)	
Engine lubrication	Splash	High Altitude Carburetor Kit* (A069E131)	
Recommended oil	SAE 10W30	High Altitude Fuel Switch Kit** (A069E132)	
Oil bottle size (included)	1.16 qt / 1.1 L	Parallel Kit (A069E133)	
Oil capacity	1.16 qt / 1.1 L	Maintenance Kit (A069E134)	
Low oil shutdown	Yes	Storage Cover (A058U957)	
Fuel types	Natural gas, propane or unleaded gasoline 10% Ethanol or less	Running Cover (A076C160)	
Fuel shut off	Yes	Replacement Battery (A069G107)	
Gasoline tank capacity	7.4 gal (28 L)	Replacement Key Fob (A069G124)	

*Required for operation above 2000 ft.

**Required for propane or natural gas operation above 2,000 ft.



Cummins Inc.
Box 3005
Columbus, IN 47202-3005
U.S.A.
cummins.com
Bulletin 6653115
Produced in U.S.A. 11/25
©2025 Cummins Inc.